

Technical Information

Cofair Products, Inc. manufactures a wide range of innovative waterproofing products for the home repair and construction industries. With decades of field experience, Cofair's products are engineered for superior performance and ease of installation.

DESCRIPTION

EPDM Quick Roof Flashing Taps is uncured EPDM rubber with specially formulated butyl mastic used in applications on roofs where pipes, stacks, vents, or corners require flexible flashing products to ensure no water infiltration into the roofing system. EPDM Quick Roof Flashing Tape allows molding or slight stretching of the material then slowly cures to form. With superior tack and peel strengths, our butyl mastic remains flexible in harsh conditions and gives a permanent water tight seal. Industry standard roofing membrane cleaners and primers must be used to clean the surfaces before application.

Always clean and prime membrane using roofing industry standard products for tape applications such as F-Primer or Low VOC Tape Primer. Allow primer to dry before installing tape. Field flashing corners, stacks, vents, or other roofing installation procedures where material must be formed. Do not over stretch. Not for use in horizontal seam repairs. Application by experienced roofing professionals recommended.



PRODUCT DATA

Material Color	Black
Odor	Slight Hydrocarbon
Volatile: % by Volume	None
Solids	100%
Penetration (ASTM D 217)	100/130 mm
Adhesion	To most clean and
	dry surfaces

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user.



Resistant to: Weather, water & water vapor, (5%) acidic or basic solutions.

Effected by: Petroleum, grease, oil, solvents, vegetable oils, and animal fats.

Product Storage: Store in warehouse without excessive heat. Do NOT store long term on roof.

Shelf Life: 1 year if stored between 60° and 80° F.