

BUTYL DECK FLASH BARRIER TECHNICAL INFORMATION

Cofair Products, Inc. manufactures a wide range of innovative waterproofing products for the home repair and construction industries. With decades of field experience, Cofair's products are engineered for superior performance and ease of installation.

DESCRIPTION

Butyl Deck Flash Barrier is a self-adhering protective membrane engineered to protect decks from premature rot and corrosion. Butyl Deck Flash Barrier features a high-performance butyl hybrid adhesive with a high strength non-slip polypropylene backing. Butyl Deck Flash Barrier will self-seal around nails and fasteners to prevent water infiltration, wood rot and lumber breakdown. Product comes packaged in individually wrapped and labeled rolls.

INSTALLATION

Cut Deck Flash Barrier to the proper length and center it over the intended area of application. Remove the release paper and press in to place. To maximize adhesion, press with a small hand roller. When overlapping material from end to end, a minimum of a two-inch overlap is required.



PRODUCT DATA

Material Color	Black
Roll Size - 1-5/8"	1-5/8" x 50'
- 3-1/8"	3-1/8" x 50'
Self-seals around screws and fasteners	Yes
Peel Adhesion @ 25°F	13 lbf/in
Peel Adhesion @ 150°F	2.2 lbf/in
Application Temperature	20°F – 170°F
Service Temperature	-70°F – 200°F
VOC Free	Yes

PRODUCT NUMBERS

PRODUCT UPC CODES

3-1/8" x 50' -- BDFB350	095959015502
1-5/8" x 50' -- BDFB1550	095959035012

For the most current Installation Instructions, Technical Specifications and Approvals, visit www.Cofair.com.

