



# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 07-Dec-2016

Revision Date 31-Oct-2018

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** QUICK ROOF ULTRA BOND SEAM PRIME/ADHESION ENHANCER - AEROSOL

### Other means of identification

**Product Code** SP14  
**UN/ID no.** UN 1950  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Adhesion promoter.  
**Uses advised against** For exterior use only. Do not use indoors.

### Details of the supplier of the safety data sheet

**Manufacturer Address** R.M. Lucas Company  
3211 South Wood Street  
Chicago, Illinois 60608  
(773) 523-4300

Prepared For: Cofair Products, Inc  
6135 Monroe Ct.  
Morton Grove, IL 60053  
847-626-1500

### Emergency telephone number

**Emergency Telephone** Call CHEMTREC Day or Night:  
Within USA and Canada: 1-800 424-9300  
Outside USA and Canada: 1-703-527-3887

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosol	Category 2
Flammable aerosol	Category 1

### Label elements

<b>Danger</b>	<b><u>Emergency Overview</u></b>
<b>Hazard statements</b> Causes skin irritation May cause genetic defects May cause cancer Suspected of damaging fertility or the unborn child May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways	

Highly flammable liquid and vapor  
Extremely flammable aerosol  
Pressurized container: May burst if heated



**Appearance** Aerosol spray can

**Physical state** Liquid

**Odor** Solvent (Mineral Spirits)

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Wash face, hands and any exposed skin thoroughly after handling  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed when product is not in use.  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
Specific treatment (see first aid information on this label)  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Call a POISON CENTER or doctor if you feel unwell  
IF SWALLOWED: Immediately call a POISON CENTER or doctor  
Do NOT induce vomiting  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### **Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards Not Otherwise Classified (HNOC)**

Not Applicable

#### **Other Information**

May be harmful in contact with skin  
Toxic to aquatic life with long lasting effects  
Unknown acute toxicity                      100% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

**Mixture**

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Common name** Asphalt Roof Primer.  
**Chemical nature** Organic solvents and additives.

Chemical Name	CAS No.	Weight-%	Trade Secret
Hexane	110-54-3	60 - 70%	*
N-Butane	106-97-8	10 - 20%	*
Propane	74-98-6	10 - 20%	*
Hydrocarbon Resin	69430-35-9	0 - 10%	*
Styrene/Butadiene Copolymer	66070-58-4	0 - 10%	*

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice** Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

**Eye contact** In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**Skin contact** Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.

**Inhalation** Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.

**Ingestion** Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.

**Self-protection of the first aider** First aider: Pay attention to self-protection!.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** May cause skin irritation. May cause eye irritation.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Sealed container may rupture/burst when heated or exposed to excessive heat.

**Hazardous combustion products** Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

**Explosion data**

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

**Other Information** Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

**For emergency responders** Use personal protection recommended in Section 8.

**Environmental precautions**

**Environmental precautions** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.

**Methods for cleaning up** Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.

**Incompatible materials** Strong acids. Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

No ACGIH or OSHA PEL is assigned to this mixture. Exposure limits for the component materials are shown below. This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA. .

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering Controls**

Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of asphalt vapors. Ventilation must be sufficient to maintain asphalt vapor concentrations below the TWA limits outlined above.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin and body protection**

Wear protective gloves and protective clothing that is resistant to chemical penetration.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations**

Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state**  
**Appearance**  
**Color**

Liquid  
Aerosol spray can  
Black

**Odor**  
**Odor threshold**

Solvent (Mineral Spirits)  
1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.

## QUICK ROOF ULTRA BOND SEAM PRIME

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting point/freezing point	Not applicable °C Not applicable °F	Not applicable
Boiling point / boiling range	> 69 °C / °F	Not applicable
Flash point	> -23 °C / > -9 °F	Setaflash
Evaporation rate	8.1	Butly acetate = 1
Flammability (solid, gas)	No information available	Not applicable
Flammability Limit in Air		No data available.
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	140	@ 20 °C
Vapor density	3	Where: Air = 1 at 68 degrees F (20 degrees C)
Specific Gravity	.7	C) Water = 1g/ml
Water solubility	Insoluble	
Solubility in other solvents	Soluble in aromatic and aliphatic solvents.	
Partition coefficient	No information available	.
Autoignition temperature	225 °C / 437 °F	
Decomposition temperature	No information available	No information available
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	Vapor accumulation could flash or explode if ignited.	
Oxidizing properties	None	
<u>Other Information</u>		
Softening point	Not applicable	
Molecular weight	No information available	
VOC Content (%)	No data available.	
Density	5.8 lb./gal	
Bulk density	Not applicable	

## 10. STABILITY AND REACTIVITY

Reactivity  
Not applicable Not applicable

### Chemical stability

Stable.

### Possibility of Hazardous Reactions

None under normal use.

**Hazardous polymerization** Hazardous polymerization does not occur.

### Conditions to avoid

Avoid static discharge. Avoid heat, sparks, and open flame.

### Incompatible materials

Strong acids. Strong oxidizing agents.

### Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Product Information** Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

**Inhalation** Avoid breathing vapors or mists.

**Eye contact** Avoid contact with eyes. Contact with eyes may cause irritation.

**QUICK ROOF ULTRA BOND SEAM PRIME**

---

**Skin contact** May cause irritation.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

**Component Information** \* The IARC Monograph (Vol. 103, 2013, Bitumen and Bitumen Emissions) defines Asphalt as 'Group 2B, Possible Carcinogen to Humans'. This definition is based on studies of exposure to Asphalt fumes at elevated temperatures. The Monograph states that temperature plays an important role in determining the degree of exposure and also the carcinogenic potential of bitumen emissions. This same Monograph states that Asphalt is non volatile at ambient temperature. There is no data presented in the Monograph to demonstrate that Asphalt at ambient temperature is considered a carcinogen. Since the normal use of this product is at ambient temperature, the Asphalt used in this product is not listed as a carcinogen. No other national or international agency has defined Asphalt as a carcinogen.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane 110-54-3	=25 g/kg ( Rat )	=3000 mg/kg ( Rabbit )	=48000 ppm ( Rat ) 4h
N-Butane 106-97-B	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
Propane 74-98-6	-	-	=658 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Can cause skin irritation.  
**Serious eye damage/eye irritation** Irritating to eyes.  
**Irritation** Irritating to eyes, respiratory system and skin.  
**Corrosivity** Not classified.  
**Sensitization** May cause sensitization of susceptible persons.  
**Germ cell mutagenicity** This product does not contain any ingredients that cause germ cell mutagenicity.  
**Carcinogenicity** This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

**Legend**  
**Reproductive toxicity** None known for product as a whole.  
**Developmental Toxicity** None known for product as a whole.  
**Teratogenicity** None known.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - No information available**

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

**ATEmix (oral)** 19,115.00  
**ATEmix (dermal)** 2,960.00  
**ATEmix (inhalation-vapor)** 44,571.00

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

30 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Hexane 110-54-3	-	2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

D001

Chemical Name	California Hazardous Waste Status
Hexane 110-54-3	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. UN 1950  
 Proper shipping name Aerosol  
 Hazard Class 2.1  
 Packing Group NA

**TDG**

UN/ID no. NA 1950  
 Proper shipping name Aerosols  
 Hazard Class 2.1  
 Packing Group NA

**MEX**

UN/ID no. NA 1950  
 Proper shipping name Aerosol  
 Hazard Class 2.1

## QUICK ROOF ULTRA BOND SEAM PRIME

---

### ICAO (air)

UN/ID no. UN 1950  
Hazard Class 2.1

### IATA

UN/ID no. UN 1950  
Hazard Class 9

### IMDG

UN/ID no. 1950  
Proper shipping name AEROSOLS  
Hazard Class 2.1

### RID

Not applicable in the United States. Not regulated.

### ADR

Not applicable in the United States. Not regulated.

### ADN

Not applicable in the United States. Not regulated.

## 15. REGULATORY INFORMATION

### International Inventories

#### TSCA

All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

#### DSL/NDSL

All of the components of this product are listed on the DSL.

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No

#### Chemical Name

Hexane – 110-54-3

#### SARA313 – Threshold Values %

1.0

#### Reactive Hazard

No

### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

## QUICK ROOF ULTRA BOND SEAM PRIME

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane 110-54-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

### US State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

This product contains the following substances regulated by various State Right-to-Know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane 110-54-3	X	X	X
N-Butane 106-97-8	X	X	X
Propane 74-98-6	X	X	X

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

### 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<b>NFPA</b>	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 2	Flammability 4	Physical hazards 0	Personal protection -

*Chronic Hazard Star Legend*

\* = Chronic Health Hazard

<b>Prepared By</b>	Prepared by Robert Barry
<b>Issue Date</b>	07-Dec-2016
<b>Revision Date</b>	31-Oct-2018

#### **Revision Note**

No information available

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**