

Cofair Products, Inc. manufactures a wide range of innovative waterproofing products for the home repair and construction industries. With decades of field experience, Cofair's products are engineered for superior performance and ease of installation.

## DESCRIPTION

Quick Roof Butyl Seam Tape is a butyl sealer used for bonding various roofing membranes together in typical seam applications in the roofing industry. Long term heat and chemical resistance gives Butyl Seam Tape the ability to remain flexible in harsh conditions. Surpassing the industry standards for tack and shear strength our Butyl Seam Tape provides superior holding power for long life and high durability. Used with typical roofing membranes such as EPDM, and TPO and some PVC membranes, Quick Roof Butyl Seam Tape allows for quick installation without expensive hot air welders. Industry standard roofing membrane cleaners and primers must be used to clean the membrane before application. Available in black or white.

## INSTALLATION

Always clean and prime membrane using roofing industry standard products for tape applications such as F-Primer or Low VOC Tape Primer. Allow primer to dry before installing tapes. Overlap membrane based on conditions or specifications. Clean both sides of membrane in the seam. Chalk lines are recommended for aligning tape. Allow release paper to stick out 1/2" from the membrane overlap. Install tape into seam leaving release paper on the tape. Roll release paper using metal seam roller with some force perpendicular to the tape product. This helps avoid fish mouths. Start in the middle of the seam and work towards the ends. Fold top membrane piece into the release paper and THEN pull release paper off, using your hand to guide membrane carefully on to tape before final rolling with metal roller.

**Resistant to:** Weather, water & water vapor, (5%) acidic or basic solutions

**Effected by:** Petroleum, grease, oil, solvents, vegetable oils, and animal fats

**Product Storage:** Store in warehouse without excessive heat. Do NOT store long term on roof.

**Shelf Life:** 1 year if stored between 60° and 80° F.

## PRODUCT DATA

Material Color	Black Or White
Odor	Slight Hydrocarbon
Volatile: % by Volume	None
Solids	100%
Penetration (ASTM D 217)	100/130 mm
Adhesion	To most clean and dry surfaces

**NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.**

### User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

### Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user.